

POLI-FIX 3800

Product Information

Double-sided transparent adhesive tape coated with a modified acrylic adhesive.

POLI-FIX 3800 is covered with a 90 g/m² silicone-paper (white) on one side.

The acrylic adhesive has an excellent resistance against UV, aging and humidity.

Especially to be emphasised are the following properties:

- Mounting of digital prints, photos and posters on various surfaces
- · Suitable for universal use

Storage Durability

Can be stored for 2 years in original packing at $20-25^{\circ}$ C and 50% humidity.

Technical Data

Carrier: PET-Film, transparent

Adhesive: Acrylic, modified

Liner: Silicone-paper, white (90 g/m²)

Adhesion [N/cm]: 3,00 + /-10%

Thickness [mm]: 0.067 + -5%

Temperature

resistance [°C]: -20 / +80

Standard Dimensions

1.050 mm x 50 m

1.260 mm x 50 m

1.372 mm x 50 m

1.524 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17 53424 Remagen – GERMANY

Phone: +49 (0) 2642 - 9836 0 Fax: +49 (0) 2642 - 9836 37 E-Mail: info@poli-tape.de Internet: www.poli-tape.de 11/05/2017

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.